

# WOOD'S SHOP CREATIVE BUILDERS

JOSEPH WOOD

4<sup>th</sup> Generation Builder - General Contractor #523278

9209 Harness St. Spring Valley, Ca. 91977  
(619) 462-Wood (9663) joeatwoodsshop@cox.net

## Materials List Etc. for 12'x12' Straight Roof Azumaya

Buy the nicest grade of exterior-use lumber that you can afford and you'll have fewer problems with wood movement (warping, cracking Etc.). I like clear western red cedar. When you order, or hand select your Post and Beam stock, do get the grade FOHC (Free of Heart Center) if at all possible. You don't want that bulls eye anywhere in the timber because that's the most unstable part of the tree and will always warp twist and check.

Also, if your stock isn't kiln dried or well-seasoned, let your stock acclimate (stack it on stickers out of the direct sun and run a fan on it 24/7) for at least 10 days (good drying conditions) before you start cutting it, especially with the wide Rafter stock, and laminated Ridge's stock. This let's the wood start to shrink/move, and stabilize its moisture content, and any warps, crowns etc. will be seen easier before you start cutting. I always lightly sand and pre stain/seal (especially the end grain) all of my major components before installing. I like oil-based Penofin [http://www.penofin.com/products\\_bl.shtml](http://www.penofin.com/products_bl.shtml)

These Plans are based on using Surfaced 4 Sides (S4S) stock, where the thickness is 1.5" for 2x stock and 5.5" for the 6x stock. The heights are 2x4 3 1/2", 2x6 5 1/2", 2x8 7 3/8", 2x10 9 3/8", 2x12 9 3/8" etc. If your stock varies from these dimensions, do account for it when laying out..

Beams 4-4x10"x12'

Posts 4-6x8 x 12'

Ridge 2x6 1-8', 1-10', 2x10 1-8', 1-10'

Rafters 2x6-

Long Commons 6-10'

Short Commons 6-8'

Jack #1 8-6'

Jack #2 8-4'

Jack #3 8-2'

2x8 Hips 4-10'

Blocking-

2x6 108' 2x8 48'

Gable ties Ties 2x6 2-5'

Collar ties 2x4 1-6'

Rafter Ties 2x4 4-12'

Web 2x10 1-10'

**2x6 T&G Sheathing (with 5" exposure)**

**6'- 22**

**8'- 14**

**10'- 12**

**12'- 12**

**14'- 12**

**16'- 16**

**\* You could also use 5/4 skip sheathing (might bend to the curves easier), instead of solid sheathing, like they did with this**

**16x20' Straight roof <http://woodsshop.com/Azumaya/16x20/16x20.htm>**

**12'x12' Curved Roof <http://woodsshop.com/Azumaya/12x12Curved-Cash/12x12Curved.htm>**

**I like to see the shingles from underneath.**

**\* 310 square' of roofing and 38' of hip cap**